

DOCTORAL THESIS

Geometric transformation and image singularity with wavelet analysis

Sun, Lu

Date of Award:
2006

[Link to publication](#)

General rights

Copyright and intellectual property rights for the publications made accessible in HKBU Scholars are retained by the authors and/or other copyright owners. In addition to the restrictions prescribed by the Copyright Ordinance of Hong Kong, all users and readers must also observe the following terms of use:

- Users may download and print one copy of any publication from HKBU Scholars for the purpose of private study or research
- Users cannot further distribute the material or use it for any profit-making activity or commercial gain
- To share publications in HKBU Scholars with others, users are welcome to freely distribute the permanent URL assigned to the publication

Geometric Transformation and Image Singularity with Wavelet Analysis

SUN Lu

A thesis submitted in partial fulfillment of the requirements
for the degree of
Doctor of Philosophy

Principal Supervisor: Prof. TANG Yuan Yan

Hong Kong Baptist University

March 2006

Abstract

Since later 1980s, wavelet analysis has been a popular field in scientific research. Wavelet analysis has been developed relatively fast and its applications have been extended widely in many scientific fields, such as image processing, signal processing and so on, and become such a voluminous subjects in recent years. In this thesis, we are mainly concerned on the analysis of geometric transformation and image singularity with wavelet theory. This thesis is organized in two major parts, and has four main contributions. The first part consist of three main contributions and the second part possesses one.

The first part of the thesis deals with the research of geometric transformation using wavelet theory. This part consists of three main contributions, which are presented briefly below:

Dyadic and decimal wavelet transforms have been used to derive affine invariant functions. The invariant functions are based on the dyadic wavelet transform as well as decimal one of the object boundary. The boundary-based approach for processing the affine transform is reviewed, and some experimental comparisons and evaluations are provided in this thesis. Six invariant functions have been calculated using different numbers of dyadic and decimal levels. Experimental results show that the stability of these invariant functions have been successfully tested for a great number of transformations.

To improve the boundary-based approach, a region-based approach is then developed in this thesis. According to theoretical analysis, the shape transformation model can be regarded as a generation-model, and its inverse transformation can be considered to be an invariant function or normalization-model. The generation-model and normalization-model are amenable to the generation of shapes and normalization of shapes respectively. Elastic geometric transformation model, i. e. harmonic model, can transform an image into arbitrary shapes including the affine one. Harmonic model can be represented by a partial differential equation with boundary condition.

Typical numerical methods, which are available for partial differential equation such as finite element method, finite difference method and moment method are discussed. Based on the discussion, a novel approach based on wavelet analysis is proposed to handle the harmonic transformation, which is called Integral Equation-Wavelet Collocation (IEWC) method. In this approach, first, an indirect method is used so that the partial differential equation (PDE) (Laplace's equation) is changed into the form of integral equation and integral representation on boundary, which are called boundary integral equation (BIE) and boundary integral representation (BIR) respectively. In order to solve the boundary integral equation (BIE) efficiently and to get rid of the second defect in the finite element method, the boundary measure formula (BMF) is used. It changes the boundary integral equation and boundary integral representation into an integral equation and an integral representation on the whole plane R^2 rather than the special boundary. They are called plane integral equation (PIE) and plane integral representation (PIR) respectively. In this way, when boundary is changed, the program code will not to be modified at all. Then, wavelet collocation technique is used to solve the plane integral equation. In the integral equation, the integrand has a discontinuity across boundary. Hence, there is a kind of singularity in it. Fortunately, wavelets have a good property to approximate this kind of singularity. Therefore, the solution of the harmonic transformation can be found. This novel approach is the most significant contribution of this thesis.

Another novel approach to handle partial differential equation for harmonic transformation is presented in this thesis, which consists of three stages: (1) Laplace equation (LE) is converted into a boundary integral equation (BIE) by the potential theory. (2) Based on the moment method, the boundary integral equation (BIE) is changed to a dense matrix equation (DME). Using the moment method, boundary is divided into several smooth pieces. The middle point of each piece of boundary, which equals to use Kronecker delta function as the weighting function, a matrix equation can then be derived. (3) The dense matrix equation (DME) is transformed to a sparse matrix equation (SME) according to the wavelet matrix transform. It can considerably reduce the computational cost. We give two ways to construct a wavelet matrix, which are based on scalar wavelet and multi-wavelet. Almost all the scalar

wavelets, either orthogonal or bi-orthogonal ones, can be used to produce wavelet matrix in this method. However, many problems may occur, when multi-wavelet is used. In this thesis, a preprocessing called spatial balance is utilized to solve these problems.

The second part of the thesis deals with the research of image singularity with wavelet analysis. One main contribution is involved in this part.

A modified algorithm for corner detection using wavelet transform is also developed in this thesis. The modified algorithm depends on a special wavelet function, which is designed specifically for corner features. This method can utilize both the information of the local extrema and modulus of transform results to detect corners and arcs effectively.

Contents

Declaration	i
Abstract	ii
Acknowledgements	v
Contents	vi
List of Tables	vii
List of Figures	viii
List of Symbols	ix
1 Introduction	1
1.1 Wavelet Analysis and Its Application	1
1.2 Geometric Transformation of Shape	2
1.3 Singularity in Image	3
1.4 Contributions of This Thesis	4
2 Wavelet Analysis	7
2.1 Wavelet Analysis	8
2.1.1 The Continuous Wavelet Transform	9
2.1.2 The Discrete Wavelet Transform	10
2.2 Multiresolution Analysis (MRA)	11
2.2.1 Decomposition and Reconstruction of Functions in $L^2(\mathbf{R})$. . .	13
2.2.2 Implementation of Decomposition and Reconstruction	15

2.3	Two Dimensional Wavelets	19
2.4	Some Typical Wavelet Bases	20
2.4.1	Haar Wavelet	20
2.4.2	Littlewood-Paley (LP) Wavelet	21
2.4.3	Battle-Lemaré-spline Wavelet	21
2.4.4	Daubechies' Compactly Supported Orthonormal Wavelets	21
2.4.5	Coiflet	22
2.4.6	Compactly Supported Spline Wavelet	23
3	Geometric Transformation Models	24
3.1	Introduction	24
3.2	Affine Transformation Model	25
3.3	Nonlinear Models	27
3.3.1	Algorithms for Bilinear Model	28
3.3.2	Six Nodes Triangle Algorithm for Quadratic Model	31
3.3.3	Eight Nodes Quadrangle Algorithm for Bi-quadratic Model	32
3.4	Complete-elastic Model	33
3.5	Concluding Remarks	34
4	Geometric Transformation with Wavelet Analysis	35
4.1	Introduction	35
4.2	Affine Invariant Function Based on Wavelet Analysis	35
4.2.1	Affine Invariant Functions Using Dyadic Levels	36
4.2.2	Affine Invariant Functions Using Decimated Levels	41
4.2.3	Experiments and Evaluation of Affine Invariant Functions	43
4.2.4	Conclusions	60
4.3	Harmonic Geometric Transformation Model Using Wavelet Collocation	61
4.3.1	Harmonic Model	61
4.3.2	Review of the Existing Methods	62
4.3.3	Boundary Integral Method	64
4.3.4	Boundary Measure Formula	67
4.3.5	Wavelet Collocation Technique	69

4.3.6	Integral Equation - Wavelet Collocation (IEWC) Approach . .	71
4.3.7	Algorithms of the IEWC Approach	75
4.3.8	Experiments	79
4.3.9	Conclusions	82
4.4	Geometric Transformation by Moment Method with Wavelet Matrix .	84
4.4.1	Moments Method with Wavelet Matrix	84
4.4.2	Experiment Results	91
4.4.3	Conclusions	95
4.5	Comparisons	97
5	Corner Detection Based on The Constructed Wavelet Function	103
5.1	Singularity in Image	103
5.1.1	Edge Detection	104
5.1.2	Review of Corner Detection of Planar Curves	110
5.2	Corner Detection Based on The Constructed Wavelet Function	116
5.2.1	The Wavelet Function Used in Our Algorithm	117
5.2.2	Algorithm and Its Implementation	118
5.2.3	Experiments and Evaluation	120
5.2.4	Conclusions	135
6	Conclusions and Future Works	142
6.1	Conclusions	142
6.2	Future Works	145
	Bibliography	147
	Curriculum Vitae	160