

DOCTORAL THESIS

Rendezvous for cognitive radio networks

Yu, Lu

Date of Award:
2015

[Link to publication](#)

General rights

Copyright and intellectual property rights for the publications made accessible in HKBU Scholars are retained by the authors and/or other copyright owners. In addition to the restrictions prescribed by the Copyright Ordinance of Hong Kong, all users and readers must also observe the following terms of use:

- Users may download and print one copy of any publication from HKBU Scholars for the purpose of private study or research
- Users cannot further distribute the material or use it for any profit-making activity or commercial gain
- To share publications in HKBU Scholars with others, users are welcome to freely distribute the permanent URL assigned to the publication

Abstract

With the traditional static spectrum management, a significant portion of the licensed spectrum is underutilized in most of time while the unlicensed spectrum is over-crowded due to the growing demand for wireless radio spectrum from exponential growth of various wireless devices. Dynamic Spectrum Access utilizes the wireless spectrum in a more intelligent and flexible way. Cognitive radios are a promising enabler for Dynamic Spectrum Access because they can sense and access the idle channels. With cognitive radios, the unlicensed users (SUs) can opportunistically identify and access the vacant portions of the spectrum of the licensed users (PUs). In cognitive radio networks (CRNs), multiple idle channels may be available to SUs. If two or more SUs want to communicate with each other, they must select a channel which is available to all of them. The process of two or more SUs to meet and establish a link on a commonly-available channel is known as *rendezvous*.

1) **Multiple Radios for Fast Rendezvous in CRNs:** The existing works on rendezvous implicitly assume that each cognitive user is equipped with one radio (i.e., one wireless transceiver). As the cost of wireless transceivers is dropping, this feature can be exploited to significantly improve the rendezvous performance at low cost. We investigate the rendezvous problem in CRNs where cognitive users are equipped with multiple radios and different users may have different numbers of radios. We first study how the existing rendezvous algorithms can be generalized to use multiple radios for faster rendezvous. We then propose a new rendezvous algorithm, called *role-based parallel sequence* (RPS), which specifically exploits multiple radios for more efficient rendezvous. Our basic idea is to let the cognitive users stay in a specific channel in one *dedicated radio* and hop on the available channels with parallel sequences in the remaining *general radios*. We prove that RPS provides guaranteed rendezvous (i.e., rendezvous can be completed within a finite time) and

derive the upper bounds on the maximum time-to-rendezvous (TTR) and the expected TTR. The simulation results show that i) multiple radios can cost-effectively improve the rendezvous performance, and ii) the proposed RPS algorithm performs better than the ones generalized from the existing algorithms.

2) Efficient Channel-Hopping Rendezvous Algorithm Based on Available Channel Set: All the existing rendezvous algorithms that provide guaranteed rendezvous (i.e., rendezvous can be achieved within finite time) generate channel-hopping (CH) sequences based on the whole channel set. However, some channels may be unavailable (e.g., being used by the licensed users) and these existing algorithms would randomly replace the unavailable channels by the available ones in the CH sequence. This random replacement is not effective, especially when the number of unavailable channels is large. We design a new rendezvous algorithm, called *Interleaved Sequences based on Available Channel set* (ISAC), that attempts rendezvous on the available channels only for faster rendezvous. ISAC constructs an odd subsequence and an even subsequence and interleaves these two subsequences to compose a CH sequence. We prove that ISAC provides guaranteed rendezvous. We derive the upper bounds on the maximum time-to-rendezvous to be $O(|C^1||C^2|)$ ($|C^1| \leq Q, |C^2| \leq Q$), where $|C^1|$ and $|C^2|$ are the numbers of available channels of two users and Q is the total number of channels. Extensive experiments are conducted to evaluate ISAC.

3) Adjustable Rendezvous in Multi-Radio CRNs: We propose an *Adjustable Multi-Radio Rendezvous* (AMRR) algorithm which exploits multiple radios for fast rendezvous based on available channels only. Suppose that a cognitive user is equipped with R radios. Our basic idea is to partition the radios into two groups: k *stay radios* and $(R - k)$ *hopping radios*. The user stays on specific channels in the stay radios while hops on its available channels parallelly in the hopping radios. We prove that the maximum time-to-rendezvous (MTTR) of AMRR is upper-bounded by $O(\frac{|C^1||C^2|}{R_1R_2})$, where $|C^1|$ and $|C^2|$ are the numbers of available channels of two users and R_1 and R_2 are the numbers of radios of the two users. This bound meets the

lower bound of MTTR of any deterministic rendezvous algorithm when two users are equipped with the same number of radios (i.e., $R_1 = R_2$). AMRR is *adjustable* in giving its best performance on either MTTR or $E(\text{TTR})$ by adjusting value of k . Simulation results show that AMRR performs better than the state-of-the-art.

4) **Cooperative Rendezvous in Multi-User CRNs:** The existing rendezvous algorithms implicitly assume that only one pair of users send handshaking messages for rendezvous at a time. In practice, more than one pair of users may go through the rendezvous process at about the same time and their handshaking messages may collide with each other. As a result, the rendezvous performance would degrade. We propose to turn this disadvantage (i.e., multiple users cause multiple access interference to each other) into an advantage (i.e., multiple users *cooperate* with each other for fast rendezvous). Specifically, we propose a *Cooperative Rendezvous Protocol* (CRP) where multi-pair users are cooperative to relay the channel information to speed the rendezvous efficiently. If one user gets the channel information of its intended rendezvous user, it can change the channel set and only hop on the commonly-available channels between itself and its intended rendezvous user. CRP can be applied in conjunction with any existing rendezvous algorithm. We prove that CRP can decrease the expected time-to-rendezvous (TTR). The simulation results show that: i) When there are multiple pairs of users, the rendezvous performance is significantly degraded because of collision, and ii) CRP can effectively counteract the collision and significantly improve the rendezvous performance.

Table of Contents

Declaration	i
Abstract	ii
Acknowledgements	v
Table of Contents	vi
List of Tables	x
List of Figures	xi
List of Symbols	xiv
List of Abbreviation	xv
Chapter 1 Introduction	1
1.1 Cognitive Radio Networks	1
1.2 Rendezvous in Cognitive Radio Networks	2
1.3 Contributions	4
1.3.1 Multiple Radio for Fast Rendezvous in Cognitive Radio Networks	4
1.3.2 Channel-Hopping Based on Available Channel Set for Rendezvous of Cognitive Radios	8
1.3.3 Adjustable Rendezvous in Multi-Radio Cognitive Radio Networks	9
1.3.4 Cooperative Rendezvous in Multi-User Cognitive Radio Networks	10
1.4 Dissertation Outline	12

Chapter 2 Literature Review	13
2.1 Taxonomy of Existing Rendezvous Algorithms	13
2.1.1 Architecture: centralized/decentralized	13
2.1.2 Common control channel (CCC): used/not used	13
2.1.3 Applicable models: symmetric/asymmetric	14
2.1.4 Maximum Time-To-Rendezvous (MTTR): finite/infinite	15
2.1.5 Based on Available/Whole Channel Set	16
2.2 Algorithms for Blind Rendezvous	17
2.2.1 Algorithms that require time-synchronization	17
2.2.2 Algorithms that do not require time-synchronization	18
2.2.3 Other additional requirements	19
Chapter 3 Multiple Radios for Fast Rendezvous in Cognitive Radio Networks	21
3.1 System Model and Problem Formulation	21
3.2 Solutions	23
3.2.1 Generalized Random Algorithm	23
3.2.2 Generalized Existing Rendezvous Algorithms	25
3.2.3 New Algorithm	32
3.3 Simulation	39
3.3.1 Effectiveness of Proposed Approach	41
3.3.2 Property of Proposed Approach: Influence of Radio Allocation	44
3.3.3 Property of Proposed Approach: Influence of G for Fixed θ . .	50
3.3.4 Performance of Generalized Algorithms and Proposed Algorithm	51
3.4 Chapter Summary	55
Chapter 4 Efficient Channel Hopping Rendezvous Algorithm Based on Available Channel Set	57
4.1 System Model And Problem Definition	57
4.2 Algorithm Design	58

4.3	Algorithm Analysis	62
4.4	Simulation	68
4.4.1	Effectiveness of ISAC	68
4.4.2	Influence of m or n for fixed Q	73
4.4.3	Influence of G for fixed m	73
4.5	Chapter Summary	75

Chapter 5 Adjustable Rendezvous in Multi-Radio Cognitive Radio Networks 77

5.1	Adjustable Multi-Radio Rendezvous Algorithm	77
5.2	Algorithm Analysis	80
5.3	Simulation	87
5.3.1	Performance of different allocations of stay radios (k)	88
5.3.2	Comparisons of different algorithms	89
5.4	Chapter Summary	91

Chapter 6 Cooperative Rendezvous in Multi-User Cognitive Radio Networks 94

6.1	System Model	94
6.2	Protocol Description	96
6.3	Protocol Analysis	100
6.3.1	The expectation of G	101
6.3.2	The fitting of the expected latency of P1 and P2 (L_1)	101
6.3.3	The analysis of Random Algorithm	102
6.3.4	The analysis of a general existing algorithm which is based on available channel set	105
6.4	Simulation	108
6.4.1	Collision evaluation	108
6.4.2	Performance of Cooperative Rendezvous Protocol.	109
6.5	Chapter Summary	114

Chapter 7 Conclusions	117
7.1 Contributions	117
7.2 Possibilities for Future Work	118
Bibliography	120
Curriculum Vitae	125