

## MASTER'S THESIS

### Characteristics of plasmonic waveguide coupling and propagation

Wang, Zilan

*Date of Award:*  
2012

[Link to publication](#)

#### General rights

Copyright and intellectual property rights for the publications made accessible in HKBU Scholars are retained by the authors and/or other copyright owners. In addition to the restrictions prescribed by the Copyright Ordinance of Hong Kong, all users and readers must also observe the following terms of use:

- Users may download and print one copy of any publication from HKBU Scholars for the purpose of private study or research
- Users cannot further distribute the material or use it for any profit-making activity or commercial gain
- To share publications in HKBU Scholars with others, users are welcome to freely distribute the permanent URL assigned to the publication

# **Characteristics of Plasmonic Waveguide Coupling and Propagation**

**WANG Zilan**

A thesis submitted in partial fulfillment of the requirements  
for the degree of  
Master of Philosophy

**Principal Supervisor: Prof. CHEAH Kok Wai**

Hong Kong Baptist University

December 2011

# Abstract

Surface plasmon polariton (SPP) offers the potential to produce novel devices for integrated optical circuit with promising characteristics of nano size chip dimension and faster operation speed comparing with traditional photonics and electric devices.

The study and generation of SPP can be achieved via silver gratings. In this thesis, the design and parameters of the device, such as the grating period, the layers of the device are studied and optimized through theoretical calculations and simulations. We then fabricate the devices using electron beam lithography, and used for optical characterization methods, such as reflection, transmission spectroscopy and ellipsometry to study their optical properties. The experimental results are compared with theoretical predictions.

In addition, the propagation properties are investigated by a simple plasmonic device which contains silver gratings to achieve SPP incoupling, propagation and outcoupling. The propagation of SPP in dielectric medium has important application such as the dielectric loaded surface plasmon waveguide. Therefore, we studied the combination of grating coupled SPP and waveguide. The guided mode inside the dielectric layer which is sandwiched between metal and air can be selected by tuning the grating period. The guided modes are calculated by effective refractive index method. The fluorescent dye can act as the indicator of SPP propagating in the waveguide layer.

Finally, we propose a novel surface plasmon resonance sensor by combining the SPP components that have been studied. In future work, the performance of the device will be demonstrated and enhanced by experiments.

# Table of Contents

Declaration	i
Abstract	ii
Acknowledgements	iii
Table of Contents	iv
List of Figures	vii
List of Tables	xii
Chapter 1 Introduction and Literature Review	
1.1 Introduction on surface plasmon polariton	1
1.2 SPP observation using fluorescence method	1
1.3 Extraordinary optical transmission	2
1.4 SPP coupling efficiency	3
1.5 Dielectric loaded SPP Waveguide	4
1.6 Plasmonic sensor	7
1.6.1 Conventional SPR sensor: the Kretschmann configuration	7
1.6.2 Grating coupled SPR sensor	8
1.6.3 Waveguide coupled SPR sensor	8
1.7 Outline of this thesis	9
Chapter 2 Theoretical background and COMSOL simulation	
2.1 Dispersion of SPP	10
2.2 SPP excitation by photons	13
2.3 Relation between grating period and incident light wavelength	15
2.4 Important concepts in SPP	16
2.4.1 Propagation length of the SPP	16

2.4.2	Skin depth of SPP field	17
2.4.3	Spectroscopic phenomena of SPP	17
2.5	Planar waveguide theory	18
2.6	Finite element method simulation of grating coupling	19
2.6.1	COMSOL simulation	20
2.6.2	Simulation of transmittance	20
2.6.3	SPP propagation	21
2.6.4	SPP incoupling and outcoupling at Ag/PMMA interface	22
2.6.5	Waveguide coupling simulation	25
2.7	Summary	29

### Chapter 3 Experiment preparation

3.1	Fabrication	30
3.1.1	Thermal evaporation	30
3.1.2	Spin coating	31
3.1.3	Electron beam lithography	32
3.1.4	Focused Ion Beam (FIB) patterning	34
3.2	Optical characterization	34
3.2.1	Reflection and transmission spectrum	34
3.2.2	Ellipsometry	36
3.2.3	Microscopic observation of SPP propagation	37
3.2.4	Fluorescence imaging	37
3.2.5	Waveguide propagation observation by fluorescence imaging	38

### Chapter 4 Surface plasmon generation and manipulation

4.1	Introduction and design	40
4.2	Spectroscopic demonstration of grating coupled SPP by normal incident	42
4.3	The grating samples in ellipsometer system	45

4.4	Angle resolved transmission	49
4.5	Summary	50
Chapter 5 Dielectric loaded waveguide coupling and propagation		
5.1	Introduction and design	51
5.2	Experimental demonstration of SPP propagation	53
5.3	Dielectric loaded waveguide	55
5.4	Effective refractive index in thin film	56
5.5	Grating coupling waveguide mode	59
5.6	Summary	62
Chapter 6 Conclusion and future work		
6.1	Conclusions	63
6.2	Future work	64
	Reference	67
	Curriculum Vitae	69