

DOCTORAL THESIS

Improved localization of neural sources and dynamical causal modelling of latency-corrected event related brain potentials and applications to face recognition and priming

Kashyap, Rajan

Date of Award:
2015

[Link to publication](#)

General rights

Copyright and intellectual property rights for the publications made accessible in HKBU Scholars are retained by the authors and/or other copyright owners. In addition to the restrictions prescribed by the Copyright Ordinance of Hong Kong, all users and readers must also observe the following terms of use:

- Users may download and print one copy of any publication from HKBU Scholars for the purpose of private study or research
- Users cannot further distribute the material or use it for any profit-making activity or commercial gain
- To share publications in HKBU Scholars with others, users are welcome to freely distribute the permanent URL assigned to the publication

Abstract

Event related potentials (ERPs) are obtained from noninvasive electroencephalograms (EEG) which measure neuronal activity of brain on the scalp. However, conventional ERPs derived by averaging of single EEG trials have strong latency variability and are smeared, resulting in blurred scalp topography, especially in late components of ERP. The smearing problem had been addressed by reconstructing ERPs after latency correction with a new EEG analysis method Residue Iteration Decomposition (RIDE), which was demonstrated in a face priming paradigm to improve distinctness in scalp topography (Ouyang et al., 2011). This thesis aims to (1) extend the benefits of RIDE to neural source space by localizing the neural generators of ERPs, thereby developing an integrated RIDE framework for improvement in source localization and causal modeling of effective source networks, and (2) apply the framework to the face priming paradigm for famous faces, to explore the dynamics of face processing and priming.

We localized sources through brain electrical source analysis for both conventional ERP and RIDE derived ERPs (RERPs). RERPs allowed localization of an additional motor execution source (Premotor Cortex, PMC), apart from 5 other common sources, of which 2 (Occipital Lobe, OL; Fusiform Gyrus, FG) were obtained from early activity (< 250 ms) and 3 (Mediotemporal lobe, MTL; Prefrontal Cortex, PFC; Anterior Temporal Lobe, ATL) from late activities (> 250 ms) of RERPs respectively. Priming effects, i.e., the difference between primed famous (PF) and unprimed famous (UF) face conditions in source waveforms (SWFs), were extended and enhanced in RERPs, especially for late sources. The priming effects revealed (1) the role of sources in each hemisphere that play in perception, memory and execution, (2) parallel processing of information in sources, (3) early processing in the right hemisphere, and (4) predominance of the right hemisphere in face recognition.

Results confirmed SWFs of RERPs as better choice for the dynamic causal model (DCM). Two candidate DCM models, forward (F) and forward-backward (FB) were outlined on each hemisphere with SWFs from PF and UF conditions of RERP data. Priming has tendency to facilitate the FB model in the left hemisphere. On the other hand, independent of model preference, priming strengthened a bidirectional connection between FG and PFC in both hemispheres; this indicates a strong role of FG in structural representation and of PFCs in controlling decisions about face familiarity. Priming modulates the pathway $FG \rightarrow MTL \rightarrow PFC$

differently in the two hemispheres, strengthening the involvement of MTL in the left hemisphere and weakening in the right hemisphere. This indicates proficiency of the left and right MTL in processing different aspects of facial information. Further, a backward connection ATL→PFC in the left hemisphere was found to be functionally relevant for both conditions in speeding up response time in individual subjects, reinforcing the role of PFC in executive functioning and ATL in naming of famous faces.

Thus, an integrated framework of source localization and DCM with RERPs allows a novel, comprehensive understanding of time resolved dynamics in face recognition and priming, thereby piloting prospects of its application to other experimental paradigms.

TABLE OF CONTENTS

Declaration	i
Abstract	ii
Acknowledgement	iv
List of Tables	ix
List of Figures	x
List of Abbreviations	xviii
Chapter 1 Introduction	1
1.1 Background	1
1.2 Motivation	3
1.3 Objectives	6
1.4 Scope and Organization of the Thesis	6
Chapter 2 Face Recognition and Priming: Motivation and Background	7
2.1 Importance of face recognition	7
2.2 Anatomy of brain involved in face recognition	8
2.3 Prior models of face recognition and priming	11
2.3.1 Functional models of face recognition and priming	11
2.3.2 Neuro-Anatomical model of face recognition	13
2.3.3 Some earlier models on face network	14
2.4 Limitations of earlier works	17
2.5 Face recognition areas from ERPs	18
2.6 Lateralization of areas and their roles in face recognition	19
2.7 Summary	21

Chapter 3 Methodology of Research	23
3.1 Basic of EEG and ERP	23
3.1.1 EEG	23
3.1.2 ERP	25
3.1.3 Limitations of ERP	27
3.1.4 RIDE	30
3.1.5 RIDE derived ERPs (RERPs)	32
3.2 Basics of source localization	35
3.2.1 Dipoles in the head	36
3.2.2 Spatio-temporal model fit	38
3.2.3 Focal Source Localization	39
3.2.4 Basics of BESA	40
3.2.5 Source waveforms (SWFs)	43
3.3 Basics of Dynamic causal model (DCM)	44
3.3.1 Basics of cortical structure and underlying dynamics of DCM	44
3.3.2 Model construction	46
3.3.3 Model selection and Comparision	47
3.4 Overview of integrated Framework	48
3.5 Summary	53
Chapter 4 Data Acquisition and RIDE analysis	55
4.1 Experiment and conventional ERPs	55
4.2 Conventional ERP and their components	57
4.3 Previous RIDE analysis	58
4.4 RIDE derived ERPs (RERPs)	60
4.5 Summary	63
Chapter 5 Implementation, Result, and Discussion	65
Part I: Source Localization	65
5.1 Implementation of Source localization	65

5.2 Results of source localization	67
5.3 Source waveform (SWF) analysis	70
5.4 Priming effects in SWFs	72
5.5 Discussion	77
5.5.1 Source localization	77
5.5.2 Localizing priming effects	79
5.6 Summary	85
Chapter 6 Implementation, Result, and Discussion	88
Part II: DCM Effective Network for Face Recognition and Priming	88
6.1 Implementation of DCM	88
6.1.1 Source localization	89
6.1.2 Source waveform (SWF) analysis	89
6.1.3 Priming effects in the SWFs	90
6.1.4 DCM- model construction	91
6.1.5 DCM- connection parameters	95
6.2 Results	96
6.2.1 Preferred model	96
6.2.2 Brain-Behaviour relationship	97
6.2.3 DCM – connection parameters	100
6.3 Discussion	106
6.3.1 The face processing network	107
6.3.2 Is priming related to a general preference for FB models?	109
6.3.3 Connection strength modulations responsible for priming effects?	110
6.3.4 Global speed – up when FB model is preferred in left hemisphere	113
6.3.5 Open question and limitations	114
6.4 Summary	114
Chapter 7 Summary and Prospects	117
7.1 Summary	117
7.2 Advantages of the present work	122

7.3 Limitations of the work	124
7.3.1 Limitations of the integrated framework	124
7.3.2 Limitations in the available data	125
7.4 Future perspectives	126
7.5 General Conclusion	127
References	128-150